

Specifications

备注(Remark)

1.材料(MATERIAL)

胶芯:PA6T/PBT+30%G.F UL94V-0,颜色: 黑色.

Housing: PA6T/PBT+30%G.F UL94V-0,Color: Black 黄铜,

四方针:镍底30u"MIN,表面镀金0.8u"MIN

Contact: Brass,0.8u"MIN GOLD PLATING OVERALL

30u" MIN NICKEL UNDERPLATING OVER ALL

2.特性(characteristics):

额定电流: 3AMP

Raring Current: 3AMP.

接触阻抗: 20 MΩ MAX.

Contact Resistance: 20 MΩ MAX.

绝缘阻抗: 1000 MΩ MIN.

Insulating Resistance: 1000 MΩ MIN.

耐电压: AC 500V.

Withstanding Voltage:AC 500V.

温度范围:-40°C to+105°C

Temperture Range:-40°C to+105°C

Ordering Information

B190-1 XX XX X R XXX X 0


INSULATOR
MATERIAL :

A :PBT
B :PA6T
C :PA9T
D :LCP

LENGTH
OF
TERMINAL

PACKING
A:PE Bag
B:Tape & Reel
C:Tube
D:Tube+CAP
E:Tray

Contact Plating
Full Of Gold Semi-gold
A0=0.8u B0=0.8U"
A1=1u' B1=1U"
A2=1.5u B2=1.5U"
A3=2u" B3=2U"
A4=3u" B4=3U"



					operatlop		SCALE		Fit	Mxcon 深圳市镁旺电子科技有限公司 Shenzhen Meiwang Electronic Technology Co., Ltd.			
					XX	±0.25	UNIT		MM				
					XXX	±0.20	SIZE	A4	DFSIGH	江泽富		PART NO.	B190-1XXXXXRXXXX0
					XXX	±0.10	SHEET	1/1	CHECK			TITLE:	2.54MM筒牛 90度
					Angle	±3°	PROJ.	1/1	APPROLE			Customer No.	
REV	DATE	MODIFICATION DESCRIPTION			CHANGE	APPROVE	DIM	TOL					