

Specifications

备注(Remark)

1.材料(MATERIAL)

胶芯:PA6T/PBT+30%G.F UL94V-0,颜色: 黑色.

Housing: PA6T/PBT+30%G.F UL94V-0,Color: Black 黄铜,

四方针:镍底30u"MIN,表面镀金0.8u"MIN

Contact: Brass,0.8u"MIN GOLD PLATING OVERALL

30u" MIN NICKEL UNDERPLATING OVER ALL

2.特性(characteristics):

额定电流: 3AMP

Raring Current: 3AMP.

接触阻抗: 20 MΩ MAX.

Contact Resistance: 20 MΩ MAX.

绝缘阻抗: 1000 MΩ MIN.




Insulating Resistance: 1000 MΩ MIN.

耐电压: AC 500V.

Withstanding Voltage:AC 500V.

温度范围:-40°C to+105°C

Temperture Range:-40°C to+105°C



PCB LAYOUT

Ordering Information

P1XX-11 XX XX X S XXX X 0

HEIGHT OF HOUSING
15:1.5mm
20:2.0mm
25:2.5mm

NO.OF PINS
PER ROW
1~40P

INSULATOR MATERIAL:
A:PBT
B:PA6T
C:PA9T
D:LCP

LENGTH OF TERMINAL

PACKING:
A:PE Bag
B:Tape & Reel
C:Tube
D:Tube+CAP
E:Tray

Contact Plating
Full Of Gold Semi-gold
A0=0.8u B0=0.8U"
A1=1u B1=1U"
A2=1.5u B2=1.5U"
A3=2u B3=2U"
A4=3u B4=3U"

Dimension antitheses list						
ITEM	A		H		C	
Standard	6.0	5.7	1.5	2.0	2.5	3.0
Alternate						

				operatop		SCALE		Fit	Mxcon 深圳市镁旺电子科技有限公司 Shenzhen Meiwang Electronic Technology Co., Ltd.						
				XX	±0.25	UNIT		MM							
				XXX	±0.20	SIZE	A4	DFSIGH	江泽富	PART NO.	P1XX-11XXXXXSXXX0				
				XXX	±0.10	SHEET	1/1	CHECK		TITLE:	2.54MM 单排针 180度				
REV	DATE	MODIFICATION DESCRIPTION			CHANGE	APPROVE	PROJ.	APPROLE		Customer No.					
1		2	3	4	5	6	7	8	9	10					